

Show your True Colours with MaraJet DI-MS



Wide format graphics have become an innate part of modern cityscapes. The urban environmental impact on these images, however, can weaken their cause: a strong message carried by strong colour images.

MaraJet DI-MS scores not only with brilliance but high resistance levels maintain this brilliance, while precise Plug & Print calibration guarantees easy handling – for highest productivity.

MaraJet DI-MS

Beyond qualitative requirements like colour compatibility and high resistance, moderate odour has become equally important for the user. MaraJet DI-MS masters this challenge: its mild formulation ensures a comfortable working environment.

Applications

MaraJet DI-MS was specifically developed for Mimaki printers JV33/JV34, JV 5, and CJV-30.

The substrate range includes

- different qualities of PVC self-adhesive films (monomeric, polymeric, and cast PVC)
- other coated substrates like tarpaulin
- coated and uncoated fabrics
- suitable papers

Thanks to the high-quality pigmentation, an outdoor resistance of 3 years is achieved on corresponding high-grade films.

It can further be increased through an additional varnish overprint or lamination. Outdoor prints subject to mechanical stress, like fleet marking applications, require an additional lamination or varnish for protection.

For further information please refer to the Technical Data Sheet on www.marabu-inks.com

Your Benefits:

Perfectly compatible colour shades

- Plug & Print change-over without the need to adjust the colour profiles

Very good scratch and chemical resistance

- Very durable ink film allows easy handling, even on inexpensive substrates

Mild, low-odour solvents

- Very user-friendly

Very fast drying properties

- Perfectly suited for roll-to-roll print jobs

High-grade pigmentation & brilliance

- Low consumption thanks to high colour density

Enlarged colour gamut with coloured metallic effects

- Reproduction of silver, gold, bronze, and other pearlescent colours

In the event of any queries, please contact:

Technical Hotline

Phone: +49 7141 691140

technical.hotline@marabu.de